EVINRUDE® **E-TEC**® **JET SERIES**

105 HP

SPECIFICATIONS			
Engine Type	V6 60° E-TEC D.I.		
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)		
Displacement - cu in (L)	158.2 (2.6)		
Gear Ratio	1:1		
Full Throttle RPM Range	ttle RPM Range 5400-6000 RPM		
Starting	Electric		
Controls	Mechanical		
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode		
Alternator Output*	133 Amps Total / 50 Net Dedicated		
Steering	Remote		
Trim Method	FasTrak™ Power Trim and Tilt		
Trim Range	-6° to 15°		
Tilt Range	75°		
Lubrication	Multi-Point Targeted Oiling		
Oil Tank Capacity - gal (L)	Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available		
Recommended Oil	XPS Marine XD100 / XD50		
Recommended Fuel	87 Octane		
Warranty	3-Year, Non-Declining**		
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union		



COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Graphite	20 (508)	Remote	E105DPJL	427 (194)

Specifications subject to change.





^{*} Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

^{** 3-}Year, Non-Declining on engine, warranty excludes jet pump assembly.