

# 2020

# EXPEDITION® SE NEW

## PACKAGE HIGHLIGHTS

- Rotax® 600R E-TEC®, 900 ACE™ Turbo and 900 ACE™ engines
- pDrive™ clutch
- REV® Gen4 platform with wide-design bodywork
- 20-in. wide Multi-LinQ plate with 125 lb / 56.7 kg cargo capacity
- SC™-5U articulating rear suspension with locking mechanism on one side (no tool required)
- Air Control Suspension (ACS)
- 20 x 154 track choices: 1.5 in. Silent Cobra WT or Silent Ice Cobra WT or 1.8 in. Cobra WT
- Air radiator with fan
- RF D.E.S.S.™ key
- Easy Shift transmission (H-L-N) with RER™ electronic reverse (600R E-TEC) / electro-mechanical reverse (ACE™ engines)
- Removable passenger seat and with heated grips
- Ultra large LinQ utility cargo box with 135 L / 35.7 US gal of storage
- Hitch receiver with 1,500 lb / 680 kg towing capacity when equipped with an HD rear bumper. (1,200 lb / 544 kg std.)
- High capacity battery
- Forward Adjustable Riser
- 7.2-in. wide digital display
- 26.5-in. Ultra-high windshield with side deflectors
- Pivoting mirrors
- Deep snow running boards with large openings
- Heated driver's visor power outlet



EXPEDITION® SE 900 ACE™ TURBO shown

## EXTRA HIGHLIGHTS

- 900 ACE™ Turbo & 900 ACE™ with 650W magneto
- Reversible throttle lever (thumb or finger activated)
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Engine oil cooler
- High efficiency air radiator with fan

### ROTAX® ENGINE

	600R E-TEC®	900 ACE™ TURBO	900 ACE™
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3	3
Displacement	599.4 cc / 36.6 in. <sup>3</sup>	899 cc / 54.9 in. <sup>3</sup>	899 cc / 54.9 in. <sup>3</sup>
Bore	72.3 mm / 2.85 in.	74 mm / 2.9 in.	74 mm / 2.9 in.
Stroke	73 mm / 2.87 in.	69.7 mm / 2.7 in.	69.7 mm / 2.7 in.
Maximum engine speed	8,100 RPM	7,250 RPM	7,250 RPM
Carburation	E-TEC® direct injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded
Minimum octane	91	91	87
Fuel tank	42 L / 11.1 US gal	42 L / 11.1 US gal	42 L / 11.1 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.3 L / 3.5 qt	3.3 L / 3.5 qt

### COLOR

Lava Red / Black

### DIMENSIONS

Vehicle overall length	3,336 mm / 131.3 in.
Vehicle overall width	1,140 to 1,180 mm / 44.9 to 46.5 in.
Vehicle overall height	1,405 mm / 55.3 in.
Ski stance	975 or 1,020 mm / 38.4 or 40.2 in.
Ski overall length	1,049 mm / 41.3 in.
Track nominal width	500 mm / 20 in.
Track nominal length	3,923 mm / 154 in.
Track profile height	<b>38.1 mm / 1.5 in. Silent Cobra WT</b>
Optional track	<b>45.7 mm / 1.8 in. Cobra WT or 38.1 mm / 1.5 in. Silent Ice Cobra WT</b>

### POWERTRAIN

	600R E-TEC®	900 ACE™ TURBO	900 ACE™
Drive clutch type	pDrive™	pDrive™	pDrive™ with slider shoes
Driven clutch type	QRS	QRS	QRS
Engagement	<b>3,400 RPM</b>	2,200 RPM	<b>2,200 RPM</b>
Small sprocket number of teeth	<b>Lo = 3.87:1 ratio</b>	<b>Lo = 3.59:1 ratio</b>	<b>Lo = 4.24:1 ratio</b>
Large sprocket number of teeth	<b>Hi = 2.15:1 ratio</b>	<b>Hi = 2.0:1 ratio</b>	<b>Hi = 2.36:1 ratio</b>
Drive sprocket number of teeth	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line

### SUSPENSION

Front suspension	<b>RAS™ 3</b>
Front shock	Motion Control
Front suspension max. travel	210 mm / 8.3 in.
Rear suspension	SC™-5U
Center shock	Motion Control
Rear shock	ACS (Air Control Suspension)
Rear suspension max. travel	239 mm / 9.4 in.

### DRY WEIGHT

293 kg / 645 lb      315 kg / 693 lb      301 kg / 663 lb

### FEATURES

Frame	<b>REV® Gen4</b>	Riser block height	<b>Adjustable-120 mm / 4.7 in.</b>	Mirrors	Standard
Bodywork	<b>Wide design</b>	Starter	Electric	Windshield	<b>673 mm / 26.5 in.</b>
Skis	Pilot™ 7.4	Reverse	<b>RER™ (600R E-TEC®) Electro-mechanic (ACE™ engines)</b>	Runner	Square 3/8
Seating	2-up modular with underseat storage	Heated throttle lever/ grips	Standard (driver and passenger)	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	<b>U-shaped aluminum with J-hooks / Low grab handle</b>	Gauge	<b>7.2-in. wide digital display</b>	Hitch	<b>Hitch receiver</b>

©2019 Bombardier Recreational Products Inc., (BRP). All rights reserved.™, ® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada.



EXPEDITION® SE  
600R E-TEC® shown



EXPEDITION® SE 900 ACE™ shown

## FEATURE HIGHLIGHTS



### Rotax® 900 ACE™ Turbo engine

With a Rotax-built turbocharger specifically designed for the 900 ACE engine, riders get the technology they love with the reliable, powerful performance they demand in one advanced engine package.



### Easy Shift transmission (H-L-N) with push-button reverse

Easily shifts with multiple gear ratios. Built for heavy duty reliability with high load resistance and optimal lubrication. Handlebar push-button engages reverse – electronic RER™ with E-TEC engine choice, electro-mechanical with ACE™ engines.



### Ultra large LinQ utility cargo box

135 L / 35.7 US gal of lockable, weather resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16-in. LinQ positions on top for expandable accessory use.



### Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16- and 20-inch-wide LinQ accessories to maximize accessory options. Up to 125 lb (56.7 kg) cargo capacity.



### 7.2-in. wide digital display

All-digital LCD gauge with customizable display with flatter viewing angle provides riders with preferred info that's easy to see sitting or standing.

## GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard