

# 2020 TUNDRA SPORT

## PACKAGE HIGHLIGHTS

- REV-XU™ platform
- SC™-5M rear suspension
- eDrive™ 2 clutch
- 16 x 137 x 1.25 in. Cobra® track
- Lynx Telescopic front suspension
- Pilot™ DS 2 skis
- Brembo brake with braided stainless-steel brake line
- 394 mm / 15.5 in. windshield
- Analog gauge with display
- HPG™ rear shock
- Cargo rack
- Low profile 2-up seat with strap



TUNDRA™ SPORT 550 Fan shown

## ROTAX® ENGINE

	550 Fan	600 ACE™
Engine details	Axial fan-cooled, cylinder reed porting	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2
Displacement	553.4 cc / 33.8 in. <sup>3</sup>	600 cc / 36.6 in. <sup>3</sup>
Bore	76 mm / 3 in.	74 mm / 2.9 in.
Stroke	61 mm / 2.4 in.	69.7 mm / 2.7 in.
Maximum engine speed	6,800 RPM	7,250 RPM
Carburation	2X VM-30	EFI
Recommended fuel type	Regular unleaded	Regular unleaded
Minimum octane	87	87
Fuel tank	40 L / 10.6 US gal	40 L / 10.6 US gal
Oil tank capacity	3.7 L / 3.9 qt	2.1 L / 2.2 qt

## POWERTRAIN

	550 Fan	600 ACE™
Drive clutch type	eDrive™ 2	eDrive™ 2
Driven clutch type	QRS (short shaft)	QRS (short shaft)
Engagement	2,600 RPM	2,200 RPM
Small sprocket number of teeth	19	21
Large sprocket number of teeth	45	51
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line

## DRY WEIGHT

210 kg / 463 lb      221 kg / 486 lb

## FEATURES

Frame	REV-XU™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ DS 2	Reverse	RER™ (550 Fan) Mechanical (600 ACE™)	Windshield	394 mm / 15.5 in.
Seating	Low profile 2-up	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Straight aluminum with J-hooks / Grab handle	Heated grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	205 mm / 8.1 in.	Gauge	Analog with display	Hitch	Optional



TUNDRA™ SPORT 600 ACE™ shown



TUNDRA™ SPORT 600 ACE™ shown

## FEATURE HIGHLIGHTS



### Low profile 2-up seat

Capable of seating two riders for trip to the cabin, yet low profile for clearance when exploring solo.



### Finger throttle position (600 ACE™)

Throttle block can be rotated to be used as either a traditional thumb throttle or unique finger throttle.



### iTC™ with ECO® mode (600 ACE™)

The industry's only Intelligent Throttle Control (iTC™) throttle-by-wire technology. Includes three shift-on-the-fly driving modes (Sport, Standard, ECO®), Learning Key feature and optional finger throttle operation.



### Lightweight aluminum rack

50 pound (23 kg) cargo capacity.



### Analog gauge with display

## GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Optional (600 ACE™), N/A (550 Fan)