2020

GRAND TOURING SPORT

PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ and **600 ACE™** engines with 420W magneto
- \bullet RAS $^{\scriptscriptstyle{\text{TM}}}$ 3 front suspension
- REV® Gen4 platform with wide-design bodywork
- pDrive™ clutch (900 ACE™)
- SilentDrive™ system with 15 x 137 x 1.25 in. Silent Track II
- 26.5-in. Ultra-high windshield with side deflectors
- 2-up seat with heated passenger handholds and air deflectors
- · Mechanical reverse
- Reversible throttle lever (thumb or finger activated)
- Pivoting mirrors
- Heated driver's visor power outlet
- SC[™]-5M rear suspension
- Pilot™ 5.7 SL skis
- Brembo brake with braided stainless-steel brake line
- 4.5-in. digital display
- iTC™ Engine mapping modes (Standard, Sport or ECO®)



GRAND TOURING SPORT 900 ACE™ shown

ROTAX® ENGINE	900 ACE™	600 ACE™
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3	2
Displacement	899 cc / 54.9 in. ³	600 cc / 36.6 in. ³
Bore	74 mm / 2.9 in.	74 mm / 2.9 in.
Stroke	69.7 mm / 2.7 in.	69.7 mm / 2.7 in.
Maximum engine speed	7,250 RPM	7,250 RPM
Carburation	EFI	EFI
Recommended fuel type	Regular unleaded	Regular unleaded
Minimum octane	87	87
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.3 L / 3.5 qt	2.1 L / 2.2 qt
POWERTRAIN		
Drive clutch type	pDrive [™] with slider shoes	eDrive™ 2
Driven clutch type	QRS	QRS
Engagement	2,200 RPM	2,200 RPM
Small sprocket number of teeth	24	21
Large sprocket number of teeth	49	51
Drive sprocket number of teeth	16	16
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-st braided brake line

236 kg / 519 lb

COLOR

Catalyst Grey / Black	
DIMENSIONS	
Vehicle overall length	3,038 mm / 119.6 in.
Vehicle overall width	1,217 mm / 47.9 in.
Vehicle overall height	1,405 mm / 55.3 in.
Ski stance	1,077 mm / 42.4 in.
Ski overall length	1,066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3,487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. Silent Track II

SUSPENSION

Front suspension	RAS™ 3
Front shock	Motion Control
Front suspension max. travel	220 mm / 8.7 in.
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	245 mm / 9.6 in.

FEATURES

DRY WEIGHT

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 5.7 SL
Seating	2-up
Handlebar	U-shaped aluminum

Riser block height	120 mm / 4.7 in.
Starter	Electric
Reverse	Mechanical
Heated throttle lever/ grips	Standard (driver and passenger)
Gauge	4.5-in. digital display

Mirrors	Standard
Windshield	673 mm / 26.5
Runner	Round 1/2
Carbide configuration	102 mm / 4 in. at 90°
Hitch	Optional

227 kg / 498 lb



GRAND TOURING SPORT 600 ACE™ shown

FEATURE HIGHLIGHTS



iTC™ with ECO® mode

Intelligent Throttle Control (iTC TM) throttle-by-wire technology includes three shift-on-the-fly driving modes (Sport, Standard, ECO $^{\otimes}$).



Finger throttle position

Throttle block can be rotated to be used as either a traditional thumb throttle or unique finger throttle.



Ultra-high windshield

Sculpted to offer improved rider and passenger wind deflection.



2-up seat with passenger handholds

Comfortable 2-up seat with backrest, including handholds.



4.5-in. digital display

All-digital LCD gauge cluster with flatter viewing angle for an easy-to-read info center whether standing or sitting.

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard

