EVINRUDE® E-TEC® G2®

150 H.O.

SPECIFICATIONS					
Engine Type	H.O. V6 66° E-TEC G2 D.I.				
Bore x Stroke - in (mm)	3.39 x 3.10 (86 x 78.7)				
Displacement - cu in (L)	167 (2.7)				
Gear Ratio	2.17:1				
Full Throttle RPM Range	5000-6000 RPM				
Starting	Electric				
Controls	ICON II				
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode				
Alternator Output*	133 Amps Total / 50 net Dedicated / 14 amps @ idle				
Trim Method	Power Trim & Tilt				
Trim Range	-6° to 15°				
Lubrication	Multi-Point Targeted Oiling				
Oil Tank Capacity - gal (L)	On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)				
Recommended Oil	XPS Marine XD100				
Recommended Fuel	87 Octane				
Warranty	5-Year Engine** / 5-Year Corrosion				
Mounting Centers - in (mm)	Minimum 26 (660)				
Color Customization	Over 400 Color Panel Options				
Integrated Features	Dual Axis Rigging / iTrim				
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union				



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)	TILT RANGE	STEERING ANGLE
Single	Slate Gray	20 (508)	iSteer DPS	C150HGLF	530 (240)	81°	+/- 32°
			Remote	C150HGLP	496 (225)	75°	+/- 30°
		25 (635)	Remote	C150HGXP	507 (230)	75°	+/- 30°
	Classic White	20 (508)	iSteer DPS	C150HWLF	530 (240)	81°	+/- 32°
			Remote	C150HWLP	496 (225)	75°	+/- 30°
		25 (635)	Remote	C150HWXP	507 (230)	75°	+/- 30°
Single [†] / Multiple	Slate Gray	25 (635)	iSteer DPS IHS / Tiebar	C150HGXF [†] C150HGXC [‡]	541 (245) 533 (242)	81°	+/- 32°
			iDOCK iDOCK	C150HGXA C150GXCA [‡]	541 (245) 533 (242)	81°	+/- 32°
	Classic White	25 (635)	iSteer DPS IHS / Tiebar	C150HWXF [†] C150HWXC [‡]	541 (245) 533 (242)	81°	+/- 32°
			iDOCK iDOCK	C150HWXA C150WXCA‡	541 (245) 533 (242)	81°	+/- 32°

Specifications subject to change.



Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

^{** 3} years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

[†] Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK models available for multiple installation only.

[‡] Corresponding Counter Rotation model.